



A-151

Solvent Degreaser



FEATURES

- Eliminates oil, grease and other contaminants from metal parts and equipment
- Controlled evaporation increases dwell time to reduce effort in removing contaminants
- Contains no chlorinated solvents
- Non-conductive, low odor
- Conforms to VOC regulations in US and Canada
- High flash point 158°F (70°C)
- Ideal for parts washers, dip tanks, and ultrasonic cleaners
- Contoured can for improved hand grip

APPLICATIONS

- Aircraft engine components
- Bearings
- Cables
- Chains
- Dip tanks
- Electric Motors
- Gauges
- Gears
- Heavy Equipment
- High-voltage cable connections
- Parts washers
- Ultrasonic Cleaner

SPECIFICATIONS AND APPROVALS

- Airbus ABR 9-0140 Type I
- Boeing D6-17487 Rev. P
- NSF International, C1 (Aerosol)
- NSF International, C1 (Bulk)

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Odor	Characteristic.
Color	Clear water-white
Boiling Point / Range	383°F (195°C)
Flash Point	158.0°F (70.0°C) Tag Closed Cup
Evaporation Rate	< 0.1 BuAc
Flammability	Flammability limit: Lower = 0.6%, Upper = 24%
Vapor Pressure	< 0.1 mm Hg @ 20°C
Vapor density	6.1 (air = 1)
Auto-Ignition Temperature	>381.2°F (>194°C)
Viscosity	< 3 mm /s @ 25°C
VOC Content	0 % per U.S. State and Federal Consumer Product Regulations
Propellant	Carbon dioxide
Dielectric Strength	36 kV

DIRECTIONS

Aerosol: Spray on parts and equipment. Bulk: Use in dip or spray applications. Allow flushing action to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. (see Section 7 of the SDS)

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat and sources of ignition. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Aerosol - Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Europe				
04320	M04320	15 wt oz / 425 g / 498 mL	aerosol	12	15 lbs
04305		5 gal / 18.93 L	pail	1	40 lbs
04355		55 gal / 208 L	drum	1	375 lbs
	M04305	20 L	pail	1	



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved