



Cross Check™ Plus

Aviation Grade Torque Seal® - Skydrol® Resistant

HANDLING

- Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharge.

DIRECTIONS

- Knead tube before use.
- Dries to the touch in less than a minute. Full cure time: 24 hours.

STORAGE

- Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. If discarded, this product is considered a RCRA ignitable.

FEATURES

- Dries to the touch: less than a minute
- Full cure time: 24 Hours
- Visually detect loose nuts and bolts
- Use on all critical fittings and locknuts during OEM and maintenance procedures
- Perfect for use on landing gear, rotor assemblies, gearboxes, Pal Nuts and more
- Excellent for marking quality procedures
- For use in any aircraft environment with possible fluid exposure
- 2-Year shelf life
- Patent 10,934,452
- Provides warranty protection against tampering
- Meets Boeing Specification BMS8-45H, Type I/III



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid
Odor	mild
Flash Point	23.0 °F (-5.0 °C) Tag Closed Cup
Boiling Point / Range	175 °F (79.44 °C)
VOC Content	38 % w/w
Evaporation Rate	> 1
Vapor Density	> 1
Prop 65 Warning	YES

AVAILABLE IN

Cnt. Type	Units/Case	Color	Approx. Case Wt.	Part #
1 oz	24	yellow	2 lbs	83417
1 oz	24	blue	2 lbs	83418
1 oz	24	pink	2 lbs	83420



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMOM®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved