

**EFX[®]**

Solvent Degreaser



FEATURES

- Ideal for degreasing metals; safe on most plastics
- Fast-acting solvent minimizes downtime
- Fast evaporating, leaves no residue
- Power blast spray instantly removes oil, grease, wax, dirt, tar and other contaminants
- Contains no chlorinated solvents
- Contoured can for improved hand grip

APPLICATIONS

- Air Compressors
- Air Tools
- Bearings
- Bonding prep
- Chains
- Cranes
- Engines
- Forklifts
- Gears
- Machinery
- Pulleys
- Wire Cables

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Colorless
Odor	Characteristic
Boiling Point / Range	140.9°F (60.5°C)
Flash Point	21.2°F (-6.0°C) Tag Closed Cup -- dispensed liquid
Evaporation Rate	1.6 (water = 1)
Flammability	Lower: 1.5%, Upper: 9%
Vapor Density	2.8 (estimated)
Water Solubility	<10%
Partition Coefficient	>1
Auto-Ignition Temperature	582.8°F (306°C)
Viscosity	< 3 cSt @ 25°C
Percent volatile	100%
Specific Gravity	0.65 - 0.68 @ 20°C
VOC Content	Aerosol: 86.9 %, Bulk: 90%

DIRECTIONS

Apply on parts and equipment. Allow solvent to dissolve and remove contaminants. Air dry or wipe with an absorbent cloth for faster drying. If equipment is still dirty or greasy, repeat procedure.

HANDLING

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. (see Section 7 of the SDS)

STORAGE

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. (see Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
01855	55 gal / 208 L	drum	1	
01820	15 wt oz / 425 g / 588 mL	aerosol	12	15 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS[®], SCRUBS[®], DYKEM[®], Accu-Lube[®], DYMON[®], Spray Nine[®], and Cedar[®] are registered trademarks and Rustlick[™], Diamondkote[™], and MetalMates[™] are trademarks of Illinois Tool Works • All Rights Reserved