

FEATURES

- Safe on plastics
- Fast Evaporating formula that leaves no residue
- Non-Flammable
- Formulated for contact cleaning
- NSF Certified: K2 Registration #167855
- VOC Compliant in all 50 states

APPLICATIONS

- Connectors
- Electrical Contacts
- Magnetic HeadsOffice Equipment
- PrintersRelays
- Solenoids

• Printed Circuit Boards

SPECIFICATIONS AND APPROVALS

• NSF International, K2

PROPERTIES

Appearance / Physical State	al State Aerosol.		
Color	Colorless.		
Odor	Mild. Ether-like.		
Boiling Point / Range	136.4°F (58°C)		
Flash Point	None (TCC)		
Evaporation Rate	> 1 (Ethyl Ether =1)		
Vapor Density	7		
Water Solubility	< 5 % w/w		
Partition Coefficient	<1		
Density	11.60		
Heat of Combustion	< 20 kJ/g		
Percent volatile	100%		
Specific Gravity	1.39 @ 25°C		
VOC Content	42% per California Consumer Product Regulations		
Propellant	HFO-1234ze, carbon dioxide		

DIRECTIONS

DO NOT use on energized electrical equipment or equipment in operation and allow surface to dry before restart. Hold can 6-8 inches away and spray directly on surface to clean. Test on a small inconspicuous area or similar expendable component prior to use to assure material compatibility. Lubricate and protect the clean surface with your choice of LPS® lubricants and corrosion inhibitors.

HANDLING

DO NOT spray into or around ignition sources. After handling, always wash hands thoroughly with soap and water. Use only with adequate ventilation. Avoid breathing vapors or spray mists. Avoid contact with eyes, skin, and clothing. Ground and bond containers before transferring materials.

STORAGE

Keep container in a cool, dry, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

DISPOSAL

Dispose of contents in accordance to local/state/national waste disposal regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
04620	18 wt oz / 510 g / 412 mL	aerosol	12	18 lbs

